

DR-T73系列

一组转换型

71A170A153A



特性:

- 环境温度可满足+85°C/+105°C
- 广泛应用于工业、工控、汽车等领域

订购信息

触点负载




订货号	触点配置	触点负载
71A170A153A	1C/1NO	16A/250VAC
71A170A153B	1C/1NO	16A/250VAC
71A170A153C	1C/1NO	16A/250VAC
71A170A153D	1C/1NO	16A/250VAC
71A170A153E	1C/1NO	16A/250VAC
71A170A153F	1C/1NO	16A/250VAC
71A170A153G	1C/1NO	16A/250VAC
71A170A153H	1C/1NO	16A/250VAC
71A170A153I	1C/1NO	16A/250VAC
71A170A153J	1C/1NO	16A/250VAC
71A170A153K	1C/1NO	16A/250VAC
71A170A153L	1C/1NO	16A/250VAC
71A170A153M	1C/1NO	16A/250VAC
71A170A153N	1C/1NO	16A/250VAC
71A170A153O	1C/1NO	16A/250VAC
71A170A153P	1C/1NO	16A/250VAC
71A170A153Q	1C/1NO	16A/250VAC
71A170A153R	1C/1NO	16A/250VAC
71A170A153S	1C/1NO	16A/250VAC
71A170A153T	1C/1NO	16A/250VAC
71A170A153U	1C/1NO	16A/250VAC
71A170A153V	1C/1NO	16A/250VAC
71A170A153W	1C/1NO	16A/250VAC
71A170A153X	1C/1NO	16A/250VAC
71A170A153Y	1C/1NO	16A/250VAC
71A170A153Z	1C/1NO	16A/250VAC

DR-T73系列

一组转换型

7A/10A/15A

安规认证 (相关认证以第三方认证证书为准)

 CQC144032118659	 R502322130005	 E4953F8
7A 240VAC/28VDC 10A 240VAC/28VDC	7A 250VAC 10A 250VAC	10A 277VAC 15A 125VAC NO

外形尺寸 线路图及安装孔图

单位:毫米(mm)

①

②

③

④

⑤